



CL 20 FL - CL 50 FL - CL 70 FL


Frigo bibite sopra banco statico con agitatore
Static-fan assisted countertop display cooler

-
-
-
-
-
-
-

Interno in ABS termoformato
Thermoformed ABS inner liner



Termometro digitale
Digital thermometer




Porta in vetro senza cornice
Full glass frameless door




Caratteristiche / Features

Modello / Model	CL 20 FL	CL 50 FL	CL 70 FL
Temperatura / Temperature Range	0 °C / +10 °C	0 °C / +10 °C	0 °C / +10 °C
Classe Climatica / Climate Class	4	4	4
Volume Netto-Lordo / Net-Gross Volume	Lt. 20 / 35	Lt. 50 / 76	Lt. 70 / 87
Superficie Esterna / Body	Lamiera preverniciata con trattamento anticorrosione Prepainted sheet with anticorrosion treatment	Lamiera preverniciata con trattamento anticorrosione Prepainted sheet with anticorrosion treatment	Lamiera preverniciata con trattamento anticorrosione Prepainted sheet with anticorrosion treatment
Superficie Interna / Inner Liner	ABS	ABS	ABS
Termometro / Thermometer	Digitale / Digital	Digitale / Digital	Digitale / Digital
Regolatore temperatura / Controller	Meccanico / Mechanical	Meccanico / Mechanical	Meccanico / Mechanical
Spessore isolamento / Insulation thickness	mm 40	mm 35	mm 35
Sbrinamento / Defrost	Automatico a fermo compressore Automatic compressor cycle	Automatico a fermo compressore Automatic compressor cycle	Automatico a fermo compressore Automatic compressor cycle
Illuminazione / Lighting	Led su perimetro porta Led on door frame	Led su perimetro porta Led on door frame	Led su perimetro porta Led on door frame
Mensole (LxP) / Shelves (WxD)	N° 1 - mm 266/274 x 246	N° 1 - mm 366/379 x 260	N° 2 - mm 363/379 x 343
Piedi-Ruote / Feet-Rollers	4 Piedini / 4 Feet	4 Piedini / 4 Feet	4 Piedini / 4 Feet
Peso Netto-Lordo / Net-Gross Weight	Kg 15 / 16	Kg 19 / 21	Kg 24 / 26
Voltaggio / Voltage	V 220	V 220	V 220
Frequenza / Frequency	Hz 50	Hz 50	Hz 50
Refrigerante / Refrigerant	R600A	R600A	R600A
Assorbimento / Absorption	W 76	W 80	W 80
Consumo Energia / Energy Consumption	KwH/24H 0,6	KwH/24H 0,8	KwH/24H 0,8

FRONTE / FRONT



LATO / SIDE


Capienza / Capacity

Modello / Model	CL 20 FL	CL 50 FL	CL 70 FL
Btg cl. 50 / Btl cl. 50	12	20	40
Latt. cl. 33 / Can cl. 33	15	60	80

Dati indicativi e variabili a seconda dei diversi packaging
Variable data depending on the different packaging

Dimensioni mm / Dimensions mm

Modello / Model	CL 20 FL	CL 50 FL	CL 70 FL
Dimensioni Esterne (LxPxH) External Dimensions (WxDxH)	330 x 396 x 472	435 x 486 x 500	435 x 486 x 685
Dimensioni Imballo (LxPxH) Packaging Dimensions (WxDxH)	390 x 458 x 540	492 x 558 x 570	492 x 558 x 755

Dimensioni Interne mm / Inner Dimensions mm

A - Larghezza / Width	250	360	360
B - Profondità / Depth	255	340	340
C - Altezza / Height	368	380	570
D - Profondità Min. / Min. Depth	115	200	200
E - Altezza Min. / Min. Height	183	195	385

Dimensioni Personalizzazione (LxH) mm / Sticker Dimensions (WxH) mm

Lato / Side	317 x 437	407 x 467	407 x 652
Vetro / Glass	225 x 335	330 x 360	330 x 545